

# **Higher-Order Functions (Part I)**

# Why Functions as Values

- Abstraction is easier with functions as values
  - abstract over **add** and **sub** cases
  - **filter**, **map**, etc.
- What are objects? Callbacks?
- Separate **deffun** form becomes unnecessary
  - ```
{deffun {f x} (+ 1 x)}  
{f 10}  
⇒  
{with {f {fun {x} (+ 1 x)}}}  
{f 10}}
```

# FWAE Grammar, Almost

```
<FWAE> ::= <num>
          | {+ <FWAE> <FWAE>}
          | {- <FWAE> <FWAE>}
          | {with {<id> <FWAE>} <FWAE>}
          | <id>
          | {<id> <FWAE>} ?
          | {fun {<id>} <FWAE>} NEW
```

# FWAE Evaluation

10  $\Rightarrow$  10

{+ 1 2}  $\Rightarrow$  3

{- 1 2}  $\Rightarrow$  -1

{with {x 7} {+ x 2}}  $\Rightarrow$  {+ 7 2}  $\Rightarrow$  9

y  $\Rightarrow$  free identifier

{fun {x} {+ 1 x}}  $\Rightarrow$   
{fun {x} {+ 1 x}}

Result is not always a number!

; interp : FWAE? . . .  $\rightarrow$  FWAE-Value?

# FWAE Evaluation

Let's think in terms of substitution, for simplicity

```
{with {y 10} {fun {x} {+ y x}}}  
⇒ {fun {x} {+ 10 x}}
```

```
{with {f {fun {x} {+ 1 x}}}  
{f 3}}  
⇒ {{fun {x} {+ 1 x}} 3}
```

Doesn't match the grammar for <FWAE>

# FWAE Grammar

```
<FWAE> ::= <num>
          |
          { + <FWAE> <FWAE> }
          |
          { - <FWAE> <FWAE> }
          |
          { with {<id> <FWAE>} <FWAE> }
          |
          <id>
          |
          {<id> <FWAE>}
          |
          { fun {<id>} <FWAE> } NEW
          |
          { <FWAE> <FWAE> } NEW
```

# FVVAE Evaluation

```
{with {f {fun {x} {+ 1 x}}}} {f 3}  
⇒ {{fun {x} {+ 1 x}} 3}  
⇒ {+ 1 3} ⇒ 4
```

```
{ {fun {x} {+ 1 x}} 3} ⇒ {+ 1 3} ⇒ 4
```

{1 2} ⇒ *expected function*

{+ 1 {fun {x} 10}} ⇒ *expected number*

# FWAE Datatype

```
(define-type FWAE
  [num (n number?)]
  [add (lhs FWAE?)
        (rhs FWAE?)]
  [sub (lhs FWAE?)
        (rhs FWAE?)]
  [with (name symbol?)
        (named-expr FWAE?)
        (body FWAE?)]
  [id (name symbol?)]
  [fun (param-name symbol?)
        (body FWAE?)]
  [app (fun-expr FWAE?)
        (arg-expr FWAE?)])  
  
(test (parse '{fun {x} {+ x 1}})
      (fun 'x (add (id 'x) (num 1))))
```

# FWAE Datatype

```
(define-type FWAE
  [num (n number?)]
  [add (lhs FWAE?)
        (rhs FWAE?)]
  [sub (lhs FWAE?)
        (rhs FWAE?)]
  [with (name symbol?)
        (named-expr FWAE?)
        (body FWAE?)]
  [id (name symbol?)]
  [fun (param-name symbol?)
        (body FWAE?)]
  [app (fun-expr FWAE?)
        (arg-expr FWAE?)])  
  
(test (parse '{(fun (x) (+ x 1)) 10})
      (app (fun 'x (add (id 'x) (num 1))) (num 10)))
```

# FWAE-Value

```
(define-type FWAE-Value
  [numV (n number?)]
  [funV (param-name symbol?)
        (body FWAE?)])
```

# FWAE Interpreter

```
; interp : FWAE? -> FWAE-Value?
(define (interp an-fwae)
  (type-case FWAE an-fwae
    [num (n) (numV n)]
    [add (l r) (num+ (interp l) (interp r))]
    [sub (l r) (num- (interp l) (interp r))]
    [with (name named-expr body)
          (interp (subst body
                           name
                           (interp named-expr)))]
    [id (name) (error 'interp "free identifier")]
    [fun (param-name body)
         (funV param-name body)]
    [app (fun-expr arg-expr)
         (local [(define fun-val (interp fun-expr))]
                (interp (subst (funV-body fun-val)
                               (funV-param-name fun-val)
                               (interp arg-expr))))]))
```

# Add and Subtract

```
; num+ : FWAE-Value? FWAE-Value? -> FWAE-Value?  
(define (num+ x y)  
  (numV (+ (numV-n x) (numV-n y))))
```

```
; num- : FWAE-Value? FWAE-Value? -> FWAE-Value?  
(define (num- x y)  
  (numV (- (numV-n x) (numV-n y))))
```

Better:

```
; num-op :  
; (number? number? -> number?) ->  
; (FWAE-Value? FWAE-Value? -> FWAE-Value?)  
(define (num-op op)  
  (lambda (x y)  
    (numV (op (numV-n x) (numV-n y)))))  
  
(define num+ (num-op +))  
(define num- (num-op -))
```

# FWAE Subst

```
; subst : FWAE? symbol? FWAE-Value? -> FWAE?
(define (subst exp sub-id val)
  (type-case FWAE exp
    ...
    [id (name)
      (cond
        [ (equal? name sub-id)
          (type-case FWAE-Value val
            [numV (n) (num n)]
            [funV (param-name body)
              (fun param-name body) ])
        [else exp]]])
    ...)))
```

# FWAE Subst

```
; subst : FWAE? symbol? FWAE-Value? -> FWAE?
(define (subst exp sub-id val)
  (type-case FWAE exp
    ...
    [app (f arg)
          (app (subst f sub-id val)
                (subst arg sub-id val))])
    [fun (param-name body)
          (if (equal? sub-id param-name)
              exp
              (fun param-name
                    (subst body sub-id val))))]))
```

# FWAE Subst

Beware: with the implementation on the previous slide,

```
(subst {with {y 10} z}
      'z
      {fun {x} {+ x y} })
⇒ {with {y 10} {fun {x} {+ x y} }}
```

- That **y** in the function used to be a free identifier
- and now it's bound! That can't be right...
- We'll see how to fix this

# No More With

Compare the **with** and **app** implementations:

```
(define (interp an-fwae)
  (type-case FWAE an-fwae
    ...
    [with (name named-expr body)
      (interp (subst body
                      name
                      (interp named-expr)))]
    ...
    [app (fun-expr arg-expr)
      (local [(define fun-val (interp fun-expr))]
        (interp (subst (funV-body fun-val)
                      (funV-param-name fun-val)
                      (interp arg-expr))))]))
```

The **app** case does everything that **with** does

# No More With

```
{with {x 10} x}
```

is the same as

```
{ {fun {x} x} 10 }
```

In general,

```
{with {<id> <FWAE>1} <FWAE>2}
```

is the same as

```
{ {fun {<id>} <FWAE>2} <FWAE>1}
```

Aside: IIFEs in JavaScript

So let's just get rid of `with`

Don't worry, we'll bring it back

# FAE Grammar

```
<FAE> ::= <num>
         | {+ <FAE> <FAE>}
         | {- <FAE> <FAE>}
         | {with {<id> <FAE>} <FAE>}
         | <id>
         | {fun {<id>} <FAE>}
         | {<FAE> <FAE>}
```

# FAE Interpreter

```
; interp : FAE? -> FAE-Value?
(define (interp a-fae)
  (type-case FAE a-fae
    [num (n) (numV n)]
    [add (l r) (num+ (interp l) (interp r))]
    [sub (l r) (num- (interp l) (interp r))]
    [id (name) (error 'interp "free identifier")]
    [fun (param-name body) (funV param-name body)]
    [app (fun-expr arg-expr)
         (local [(define fun-val (interp fun-expr))]
                (interp (subst (funV-body fun-val)
                               (funV-param-name fun-val)
                               (interp arg-expr))))]))
```

# Where to?

- This FAE language will be our "base camp" for most of the rest of the quarter
  - We'll extend it in various ways
  - We'll use it to demonstrate concepts
- Some loose ends we need to tie up
  - Fixing substitution
  - Bringing **with** back
  - Moving to deferred substitution
  - Bringing recursion back (we "lost" it along the way)